

## POROSITY DETECTOR CALIBRATION

### Application

- Verification of output voltage and set voltage of detectors when a load is applied to the probe.
- To ensure accuracy, and to enable voltage adjustment (if necessary).

### Features

- Used for checking & calibrating Porosity Detector output voltage
- Compact, lightweight hand-held unit
- Integral probe
- Conformance Certificate
- Carry Case (36 x 29 x 18)

### DC Crest Meter Specifications

Range: 0 to 30kV  
Resolution: 10V (0 to 20kV)  
100V (0 to 30kV)

Earth Lead: Separate

Dimensions: 260 x 85 x 50mm  
Weight: 380g

### Pulse Crest Meter Specifications

Range: 5 to 30kV  
Resolution: 100V

Earth Lead: Integral

Dimensions: 300 x 75 x 40mm  
Weight: 390g



**DC Crest Meter**



**Pulse Crest Meter**

(suitable for PCWI Pulse Detectors only)

**Made in AUSTRALIA**

Certification available  
(Pulse Crest meter to 30kV only)

**PCWI International Pty Ltd**

13 Alhambra Avenue CARDIFF NSW 2285  
Ph: (02) 4954 3900 • Fax: (02) 4954 3999  
email: sales@pcwi.com.au • http://www.pcwi.com.au