



HOME
CLAMP METER
GRAPHIC RECORDER
HUMIDITY METER
HUMIDITY CALIBRATION CELL
INFRARED THERMOMETER
INSULATION TESTER
MULTIMETER
SOUND LEVEL METER
THERMOMETER
THERMO RECORDER
ACCESSORY



CENTER 320 Sound Level Meter

- IEC 651 Type II
- Level Range Display
- Simultaneous MAX MIN Measurement
- 4 digits Display
- Auto Power Off
- AC DC Signal Output
- Resolution 0.1 dB update cycle 0.5 s

Microphone:

Electrostatic condenser microphone

Accuracy:

± 1.5 dB (ref 94dB @1KHz)

Level Range:

Lo = 30 ~ 80 dB

Med = 50 ~ 100 dB

Hi = 80 ~ 130 dB

Frequency Weighting:

A , C

Time Weighting:

Fast , Slow

Auxiliary Outputs:

AC output

Output voltage: 1Vrms (at full scale)

Output impedance: Approx:600 Ω

AC output

Output voltage: 10mV / dB

Output impedance: Approx:50 Ω

Dynamic Range:

50 dB

Frequency Range:

31.5Hz to 8KHz

Battery Type:

9V Battery NEDA 1604, IEC 6F22, JIS 006P

Battery Life:

50 hours (with alkaline battery)

Operation Temp.:

0°C~ 40°C(<80% R.H.) 9V

Battery, Carrying Case, Calibration Screwdriver, Windscreen

CENTER TECHNOLOGY CORP.

4/F.,No.415,Jung-Jeng Rd.,238 Shu-Lin, Taipei, Taiwan

TEL:886-2-26763926 FAX:886-2-26763925

<mailto:athena@centertek.com>